



1 Reflected Ceiling Plan 1/4" = 1'-0"

CEILING PLAN GENERAL NOTES

1. ENGINEERING, THE REFLECTED CEILING PLAN REPRESENTS FIXTURE LOCATIONS ONLY. REFER TO ELECTRICAL ENGINEERING DOCUMENTS FOR CIRCUITING AND LOADS.
2. LOCATION AND FIELD VERIFICATION, THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFICATION OF DUCTWORK AND PLUMBING LINES TO INSURE INSTALLATION OF LIGHT FIXTURES SHOWN. CONTRACTOR SHALL NOTIFY ARCHITECT/DISEIGNER OF ANY OBSTRUCTIONS PROHIBITING LIGHT FIXTURES FROM BEING LOCATED AS SHOWN ON THE REFLECTED CEILING PLAN. ANY OBSTRUCTIONS SHALL BE REMOVED FROM ARCHITECT/DISEIGNER FOR THE REVISED FIXTURE LOCATION.
3. STANDARD 2 X 2 CEILING TILE IS TO BE SELECTED BY TENANT.
4. CLEAN UP, CONTRACTOR SHALL INSURE THAT LENSES, IN LIGHTING FIXTURES ARE LEFT CLEAN AND FREE OF DUST, DIRT, AND SMUDGES. PLASTIC AND LABELS SHALL BE REMOVED FROM ALL LIGHT FIXTURES AT PROJECT COMPLETION.
5. EQUIPMENT, ALL NEW OR EXISTING HVAC, ELECTRICAL, AND PLUMBING EQUIPMENT SHALL BE FREE OF DEFECTS. ANY DAMAGED OR DEFECTIVE EQUIPMENT SHALL BE REPLACED.

CEILING PLAN KEY NOTES

1. PROVIDE & INSTALL NEW 2X2 CEILING GRID. CEILING TO BE 8' X 10'-0" AFF. OPEN CEILING AT STORAGE #11 REMAIN.
2. REFER TO ENGINEERING DRAWINGS FOR HVAC AND ELECTRICAL INFORMATION
3. REFER TO ENGINEERING DRAWINGS FOR FINAL EMERGENCY LIGHT FIXTURE AND EXIT SIGNAE LOCATIONS AND INFORMATION.
4. REFER TO ENGINEERING DRAWINGS FOR FINAL LIGHTING AND ELECTRICAL SPECIFICATIONS.

SYMBOL LEGEND

- | | |
|--|---|
| | LIGHT FIXTURE - NEW 2x4' FLUORESCENT |
| | LIGHT FIXTURE - NEW 1'x6' FLUORESCENT |
| | EXHAUST FAN |
| | EMERGENCY FIXTURE - CEILING MOUNTED EXIT SIGN (24 HOUR -EMERGENCY CIRCUIT) |
| | CEILING - NEW CEILING TILE & GRID SPECIFICATION: CIRRUS BY USG WITH 15/6 GRID |